

STORMFLEX HT-B

BUTYL SELF-ADHERED UNDERLAYMENT



STORMFLEX HT-B

Stormflex HT-B is a premium, butyl-based high-temperature self-adhered roofing underlayment engineered for superior adhesion, durability, and long-term weather protection in demanding environments. Designed to perform under extreme heat, it maintains a strong, flexible bond to a wide range of substrates including metal, wood, and concrete, making it ideal for metal roofing systems and other high-temperature applications. Its advanced butyl adhesive technology delivers exceptional waterproofing and nail sealability. The self-adhering design allows for fast, clean installation without the need for mechanical fasteners, reducing labor while ensuring a consistent, high-performance barrier against moisture infiltration.

FEATURES & BENEFITS

- Superior traction surface combined with slip resistant bottom coating provides unmatched walkability in dry, wet, or cold conditions.
- Low-temperature application (10°F / -12°C)
- High-temperature flow stability (265°F / 129.4°C)
- Split release liner for easier installation
- Meets or exceeds ASTM D1970 requirements
- Extended UV Exposure Rating: 180 days
- Limited Lifetime Warranty
- Meets/Exceeds: ASTM D4869: ASTM D8257: CAN/CSA A123.3

Test/Standard

Typical Value

Roll Width	48" / 1.22 m
Roll Length	250' / 76.2 m
Roll Weight	35.0 lb / 15.9 kg
Rolls/Pallet/Truck	30 / 1200 rolls
UV Exposure (ASTM D8257)	180 Days
High-Temperature Flow Stability	265°F / 129.4°C
Peel Adhesion	56 lbf / ft
Temperature Range ASTM D1970	15°F (-9°C) to 265°F (130°C)

The data shown above is based on lab test averages from production runs. Values are typical data and not limiting specifications. All values are +/-10% variation. This report should not be considered as a warranty. The manufacturer is not responsible for the misrepresentation or misinterpretation of the data by the reader.